Aggregation, Grouping and Multiple Relation Queries

Table of contents

Today's outline . . . 1
Aggregation . . . 2
Grouping (GROUP BY) . . . 2
Question 9 — INSERT and GROUP BY . . . 3
Question 10 — HAVING clause . . . 4
Question 11 — HAVING clause application . . . 4
Multiple relation queries . . . 5
Question 12 — SQL joins . . . 7
Question 13 — Grouping with join . . . 7
Question 14 — Theta join . . . 9
Set operations . . . 9
Question 15 — UNION query . . . 11
Question 16 — UNION query (two tables) . . . 11
Summary . . . 12

Module 3, part 2. Continues 2026-03-30-basic-sql-ddl-and-dml[1], using the same Company (`Department`/`Employee`/`Sale`/`Item`/`Customer`) and Movie (`Movie`/`StarsIn`/`MovieStar`) schemas.

Today's outline

- Aggregation and grouping (`COUNT`/`SUM`/`AVG`/`MAX`/`MIN`, `GROUP BY`, `HAVING`)
- Multiple relation queries — renaming, joins, set operations

[1] courses/infs1200/2026-03-30-basic-sql-ddl-and-dml.pdf

Aggregation

Aggregates are functions that produce a **summary value** from a set of tuples:

- `COUNT` — counts the number of tuples returned.
- `SUM/AVG` — sum/average of a set of numeric values.
- `MAX/MIN` — maximum/minimum value from a set with a total ordering (the domain doesn't have to be numeric — e.g. dates, strings).

Aggregation functions can be used in the `SELECT` clause and the `HAVING` clause (below), with or without `DISTINCT`.

```
-- Total and average salary of all employees
SELECT AVG(salary), SUM(salary)
FROM   Employee;

-- Total number of employees in department 5
SELECT COUNT(*)
FROM   Employee
WHERE  dNum = 5;

-- Distinct salary count of employees in department 5
SELECT COUNT(DISTINCT salary)
FROM   Employee
WHERE  dNum = 5;
```

Grouping (GROUP BY)

An aggregate can apply to the *whole* table, but is often needed **per group** of rows — e.g. "total employees per department", "average salary per department". `GROUP BY` provides this.

```
SELECT [DISTINCT] <target list>
FROM   <table list>
[WHERE search condition]
[GROUP BY <grouping attributes>]
[HAVING <group conditions>]
[ORDER BY column [ASC|DESC] {, column [ASC|DESC]}];
```

Rule: any attribute in the `SELECT` clause must either appear in `GROUP BY`, or be wrapped in an aggregation function.

```sql
-- Total employees (no grouping)
SELECT COUNT(*) FROM Employee;                    -- 8

-- Total employees per department
SELECT dNum, COUNT(*)
FROM   Employee
GROUP BY dNum;
--  dNum | COUNT(*)
--     1 |    1
--     4 |    3
--     5 |    4

-- Total employees earning > 40000, per department
SELECT dNum, COUNT(*)
FROM   Employee
WHERE  salary > 40000
GROUP BY dNum;

-- Average salary per department, per gender
SELECT dNum, sex, AVG(salary)
FROM   Employee
GROUP BY dNum, sex;
```

`WHERE` filters *rows* before grouping; `GROUP BY` then buckets the remaining rows.

Question 9 — INSERT and GROUP BY

Given `Students [id, fName, lName, degree]`, what does `INSERT INTO DegreeStatistics (degree, num) SELECT degree, COUNT(*) FROM Students GROUP BY degree` insert?

A. `(Arts, 2), (CompSci, 3)` B. `(Math, 1), (Arts, 2), (CompSci, 3)` C. `(Math, 1), (Arts, 8), (CompSci, 12)` D. None of the above

> **i** Solution
>
> **B.** Every distinct `degree` value gets its own group and count — missing `Math` from option A is the trap (there's no `WHERE` clause excluding it). C looks like `SUM(id)` was used instead of `COUNT(*)`.

HAVING — conditions on groups

`HAVING` (following `GROUP BY`) filters *groups*, the way `WHERE` filters rows — and unlike `WHERE`, `HAVING` **can** include aggregates. Any attribute in `HAVING` must appear in `GROUP BY` or be aggregated.

```sql
-- Total employees, for departments with more than 2 employees
SELECT   dNum, COUNT(*)
FROM     Employee
GROUP BY dNum
HAVING   COUNT(*) > 2;

-- Departments with more than 2 employees earning > 20000
SELECT   dNum, COUNT(*)
FROM     Employee
WHERE    salary > 20000
GROUP BY dNum
HAVING   COUNT(*) > 2;
```

In the second example, `WHERE` and `HAVING` both operate on "employees earning > 20000" — contrast this with the correlated-subquery version of the same idea, in 2026-04-13-nested-queries-views-and-generative-ai[2], where `HAVING` checks a *different* condition across *all* employees via a subquery.

Question 10 — HAVING clause

For `SELECT team, COUNT(*) AS games_played, SUM(runsFor) AS total_runs FROM Scores GROUP BY team HAVING SUM(runsFor) > 10`*, what is the* `HAVING` *clause doing?*

A. Removes rows where `runsFor <= 10` before grouping. B. Filters rows before aggregation. C. Limits which teams are included, based on their total runs scored. D. Replaces `WHERE` for simple conditions. E. Counts opponents that allowed more than 10 runs.

> **i** Solution
>
> **C.** `HAVING` filters *groups* (here, teams) by an aggregate condition computed *after* grouping — it doesn't touch individual rows before grouping (that's what `WHERE` would do).

Question 11 — HAVING clause application

Given `Employee [id, dNum, sex, salary]` *with rows* `(1,5,M,30000), (2,5,M,40000), (3,5,F,25000), (4,5,M,38000), (5,1,M,55000),` *for* `SELECT dNum, sex, COUNT(*) FROM Employee GROUP BY dNum, sex HAVING …`*, which* `HAVING` *clause produces a* ***different*** *result from the others?*

A. `HAVING COUNT(*) < 2` B. `HAVING AVG(salary) = 25000` C. `HAVING MAX(salary) <= MIN(salary)` D. `HAVING SUM(salary) < 60000`

[2] courses/infs1200/2026-04-13-nested-queries-views-and-generative-ai.pdf

Solution

B. Groups are `(5,M)` [3 rows: 30000/40000/38000], `(5,F)` [1 row: 25000], `(1,M)` [1 row: 55000]. A, C and D all select the same two singleton groups `(5,F,1)` and `(1,M,1)` (both have `COUNT(*)=1<2`; both trivially satisfy `MAX<=MIN` since there's one value; both have `SUM<60000`). B selects only `(5,F,1)`, since its average is exactly 25000 but `(1,M)`'s average is 55000 — a different result set.

Multiple relation queries

Three tools for combining relations: **renaming**, **joins**, and **set operations** (union/intersect/difference).

Renaming

Two ways to rename: qualifying attribute names (`table.attribute`), or declaring an alias (`AS`). Renaming removes ambiguity and enables self-joins.

```
-- Names/salaries/salaries+17% for dept 4
SELECT E.name, salary, 1.17 * salary AS 'includingSuper'
FROM   Employee E
WHERE  dNum = 4;
```

Cartesian product

`R1 × R2`: every row of `R1` combined with every row of `R2`; the result schema is the concatenation of both schemas. If `|R1| = m` and `|R2| = n`, then `|R1 × R2| = m * n`.

```
SELECT *
FROM   MovieStar, StarsIn;
```

Every `MovieStar` row is paired with *every* `StarsIn` row — almost always **not** what you want (compare with a join, below).

Equi-join and joins generally

An **equi-join** combines tuples from two relations that agree on some pair of attributes (a *join condition* using only `=`). A **join** in general combines related tuples into a single result relation:

```
SELECT <attribute list>
FROM   <table> {<type of join> JOIN <table to join to> ON <join attributes>}
[WHERE search condition]

-- equivalently, using WHERE (Cartesian product + join condition):
SELECT <attribute list>
FROM   <table list of more than one table>
[WHERE join condition AND search condition]
```

```
-- Names of the managers of each department
SELECT E.name, D.dName
FROM   Department AS D, Employee AS E
WHERE  D.mgrSSN = E.ssn;

-- equivalent, using JOIN
SELECT E.name, D.dName
FROM   Department AS D
JOIN   Employee AS E ON D.mgrSSN = E.ssn;
```

`JOIN/ON` is generally preferred over the `WHERE`-based Cartesian product form because it can be more efficiently optimised by the DBMS — but for this course, they're treated as equivalent.

```
-- IDs and names of all stars who've been in a movie
SELECT DISTINCT S.starID, name
FROM   StarsIn S
JOIN   MovieStar MS ON S.starID = MS.starID;

-- IDs, names and characters of stars in the movie with movieID 1
SELECT S.starID, name, role
FROM   StarsIn S
JOIN   MovieStar MS ON S.starID = MS.starID
WHERE  S.movieID = 1;

-- Multi-join: stars in "Gone with the Wind"
SELECT S.starID, MS.name, S.role, M.title
FROM   StarsIn S
JOIN   MovieStar MS ON S.starID = MS.starID
JOIN   Movie M ON S.movieID = M.movieID
WHERE  M.title LIKE 'Gone with the Wind';
```

Question 12 — SQL joins

Which query correctly returns employee names and the name of the department they work in?

A. `SELECT e.name, d.dName FROM Employee e, Department d WHERE e.mgrSSN = d.mgrSSN;` B. `SELECT e.name, d.dName FROM Employee e JOIN Department d ON e.ssn = d.mgrSSN;` C. `SELECT e.name, d.dName FROM Department d JOIN Employee e ON d.mgrSSN = e.mgrSSN;` D. `SELECT e.name, d.dName FROM Employee e JOIN Department d ON e.dNum = d.dNumber;`

> **Solution**
>
> **D.** A joins on shared `mgrSSN` values (matching managers to managers, not employees to *their* department). B matches an employee's `ssn` to a department's `mgrSSN` — that's "departments this employee manages", not "the department they work in". C is the same mismatch as B, reversed. D correctly joins each employee's `dNum` to the department's `dNumber` — "the department they work in".

Self-joins (recursive relationships)

```sql
-- Employees who earn less than their manager
SELECT   A.name AS employee, A.salary AS employeeSalary,
         B.name AS manager, B.salary AS managerSalary
FROM     Employee A
JOIN     Employee B ON A.mgrSSN = B.ssn
WHERE    A.salary < B.salary;
```

Question 13 — Grouping with join

Given `Flight [FlightNo, Origin, Destination]`, for

```sql
SELECT F1.Origin, F2.Destination, COUNT(*)
FROM   Flight F1, Flight F2
WHERE  F1.Destination = F2.Origin
GROUP BY F1.Origin, F2.Destination
```

(read as: "how many ways can you connect from `F1.Origin` to `F2.Destination` via one stopover?") which is in the result?

A. `(Brisbane, Melbourne, 2)` B. `(Perth, Sydney, 6)` C. `(Perth, Melbourne, 1)` D. All of the above E. None of the above

Solution

D — all of the above. The self-join pairs every `F1` flight with every `F2` flight departing from where `F1` lands, then groups by `(F1.Origin, F2.Destination)` and counts the pairs. Working through all nine flights (2× Brisbane→Sydney, 1× Sydney→Melbourne, 2× Melbourne→Perth, 3× Perth→Brisbane, 1× Perth→Sydney) gives:

F1.Origin	F2.Destination	COUNT(*)	Why
Brisbane	Melbourne	2	2 Brisbane→Sydney flights × 1 Sydney→Melbourne flight
Sydney	Perth	2	1 Sydney→Melbourne flight × 2 Melbourne→Perth flights
Melbourne	Brisbane	6	2 Melbourne→Perth flights × 3 Perth→Brisbane flights
Melbourne	Sydney	2	2 Melbourne→Perth flights × 1 Perth→Sydney flight
Perth	Sydney	6	3 Perth→Brisbane flights × 2 Brisbane→Sydney flights
Perth	Melbourne	1	1 Perth→Sydney flight × 1 Sydney→Melbourne flight

`(Brisbane, Melbourne, 2)`, `(Perth, Sydney, 6)` and `(Perth, Melbourne, 1)` are all genuinely in the result — so A, B and C are all correct.

Theta-join

The most general join type — the join condition can use any of `{=, , <, , >, }`, not just `=`.

Question 14 — Theta join

Given `Student [id, sName, age]`, *for* `SELECT DISTINCT S1.sName, S1.age FROM Student S1 JOIN Student S2 ON S1.age > S2.age`, *what does this return?*

A. Name/age of one of the oldest student(s). B. Name/age of all of the oldest student(s). C. Name/age of all of the youngest student(s). D. Name/age of all students older than the youngest student(s). E. None of the above.

> **i** Solution
>
> **D.** `S1.age > S2.age` only has a match for `S1` if *some* student (`S2`) is younger — i.e. `S1` is not the/a youngest student. So the result is every student who is older than at least one other student: everyone except the youngest.

Inner and outer joins

- **Inner join** (default, just `JOIN`): a tuple appears in the result only if matching tuples exist in *both* relations.
- **Outer join**: includes the inner join result, *plus* unmatched rows from one or both tables:
  - **Left join** — all rows from the first table.
  - **Right join** — all rows from the second table.
  - **Full outer join** — all rows from both. **Not implemented in MySQL.**

```sql
-- Misses departments without a manager:
SELECT   D.dName, E.name
FROM     Department AS D
JOIN     Employee AS E ON D.mgrSSN = E.ssn;

-- Includes them (NULL for the manager's name):
SELECT   D.dName, E.name
FROM     Department AS D
LEFT JOIN Employee AS E ON D.mgrSSN = E.ssn;
```

Set operations

A relation is a *set* of tuples (no duplicates, no order) — set operators apply directly:

- **UNION** — tuples in either or both relations.
- **INTERSECT** — tuples in both.
- **EXCEPT** (a.k.a. `MINUS`) — tuples in the first but not the second.

Union compatibility is required: the same number of columns, with pair-wise compatible domains.

By default each of these eliminates duplicates; append `ALL` (`UNION ALL`, `INTERSECT ALL`, `EXCEPT ALL`) to keep multiset semantics. If a tuple occurs `m` times in `r` and `n` times in `s`: it occurs `m + n` times in `r UNION ALL s`, `min(m, n)` times in `r INTERSECT ALL s`, and `max(0, m - n)` times in `r EXCEPT ALL s`.

```
SELECT ...
UNION [ALL] SELECT ...
[UNION [ALL] SELECT ...]
```

```
-- Stars in a movie from 1944 or 1974 - via OR:
SELECT starID FROM Movie M JOIN StarsIn S ON M.movieID = S.movieID
WHERE  year = 1944 OR year = 1974;

-- ...or equivalently via UNION:
SELECT starID FROM Movie M JOIN StarsIn S ON M.movieID = S.movieID WHERE year = 1944
UNION
SELECT starID FROM Movie M JOIN StarsIn S ON M.movieID = S.movieID WHERE year = 1974;
```

`INTERSECT` is part of the SQL standard but **not implemented in MySQL** — it can be rewritten with a self-join:

```
-- Stars in a movie from BOTH 1944 and 1974:
SELECT starID FROM Movie M JOIN StarsIn S ON M.movieID = S.movieID WHERE year = 1944
INTERSECT
SELECT starID FROM Movie M JOIN StarsIn S ON M.movieID = S.movieID WHERE year = 1974;

-- Rewritten without INTERSECT, using a self-join on starID:
SELECT DISTINCT S1.starID
FROM   Movie M1
JOIN   StarsIn S1 ON M1.movieID = S1.movieID
JOIN   StarsIn S2 ON S1.starID = S2.starID
JOIN   Movie M2 ON M2.movieID = S2.movieID
WHERE  M1.year = 1944 AND M2.year = 1974;
```

```
-- Stars in a movie from 1944 but NOT 1974 (EXCEPT):
SELECT starID FROM Movie M JOIN StarsIn S ON M.movieID = S.movieID WHERE year = 1944
EXCEPT
SELECT starID FROM Movie M JOIN StarsIn S ON M.movieID = S.movieID WHERE year = 1974;
```

`EXCEPT` queries can also always be rewritten as nested queries (next lecture).

Properties of set operators

$$A \cup B = B \cup A \qquad (A \cup B) \cup C = A \cup (B \cup C)$$
$$A \cap B = B \cap A \qquad (A \cap B) \cap C = A \cap (B \cap C)$$
$$A - B \neq B - A \qquad (A - B) - C \neq A - (B - C)$$

Union and intersection are commutative and associative; difference is **neither**.

JOIN vs set operations

	Join	Set operation
Combines	Rows from many tables into new **columns**	Result-sets of `SELECT`s into new **rows**
Column count	May differ between tables	Must match
Column types	Can differ	Must be compatible
Duplicates	Kept by default	Removed by default

Question 15 — UNION query

Given `Table [A, B, C]` *with rows* `(1,X,11), (2,Y,12), (3,Y,13)`*, what does* `SELECT * FROM Table UNION SELECT a, b FROM Table WHERE b = 'X' OR c = '13'` *produce?*

> **i** Solution
>
> **D — none of the above; the query raises an error.** `SELECT *` returns 3 columns (`A, B, C`) but `SELECT a, b` returns only 2 — the two halves of the `UNION` are **not union-compatible** (mismatched column counts), so none of the listed result tables can occur.

Question 16 — UNION query (two tables)

Given `Table1 [A,B,C] = (1,X,11), (2,Y,12), (3,Y,13)` *and* `Table2 [D,E,C] = (3,X,11), (4,Y,12), (3,Y,13)`*, what does* `SELECT * FROM Table1 UNION SELECT d, e, c FROM Table2 WHERE E = 'X' OR C = 13` *produce?*

Solution

C. `Table2` rows matching `E='X' OR C=13` are `(3,X,11)` and `(3,Y,13)`; renamed to `(A,B,C)` these are `(3,X,11)` and `(3,Y,13)`. Unioned with all of `Table1` — `(1,X,11), (2,Y,12), (3,Y,13)` — and removing the duplicate `(3,Y,13)`, the result is `(1,X,11), (2,Y,12), (3,Y,13), (3,X,11)`: four rows, all of `Table1` plus the one genuinely new row `(3,X,11)`. (A is missing a row from `Table1`; B fails to remove the duplicate `(3,Y,13)`.)

Summary

You can now aggregate and group data, and query across multiple relations using renaming, joins (equi/theta/inner/outer), and set operations. Next lecture: nested queries, views, and Generative AI & SQL. See week7-tutorial-applied-class-6-aggregation-and-grouping[3], week7-tutorial-case-study-5-easydrive-insurance[4] and week8-tutorial-applied-class-7-multiple-relation-queries[5] for practice.

[3] courses/infs1200/week7-tutorial-applied-class-6-aggregation-and-grouping.pdf
[4] courses/infs1200/week7-tutorial-case-study-5-easydrive-insurance.pdf
[5] courses/infs1200/week8-tutorial-applied-class-7-multiple-relation-queries.pdf